



MATERIAL SAFETY DATA SHEET

1 CHEMICAL PRODUCT & COMPANY IDENTIFICATION

TRADE NAME(S) **KOCHKLEEN® P-02**
CAS NUMBER MIXTURE
MSDS NUMBER 32
PRODUCT CODE ND
PRODUCT USE MEMBRANE CLEANER



MANUFACTURER / SUPPLIER Koch Membrane Systems, Inc.
850 Main Street
Wilmington, MA
01887 USA

TELEPHONE NUMBERS - 24 HOUR ASSISTANCE

Chemtrec: +1(800) 424-9300 (inside USA)
+1(703) 527-3887 (outside USA)

TELEPHONE NUMBERS - GENERAL ASSISTANCE

Product Assistance +1(978) 657-4250
8 - 5, M - F, Eastern Time

For technical assistance regarding this product, please contact your local Koch Membrane Systems representative.

2 COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient Name	CAS Number	Concentration*	Exposure Limits / Health Hazards
2-HYDROXY-1,2,3 - PROPANETRICARBOXYLIC ACID	77-92-9	60 - 100 %	Total Particulate Dust: 15 mg/m ³ 8-Hour TWA (OSHA) Respirable Particulate: 5.0 mg/m ³ 8-Hour TWA (OSHA)
SODIUM HEXAMETAPHOSPHATE	10124-56-8	15 - 40 %	Total Particulate Dust: 15 mg/m ³ 8-Hour TWA (OSHA) Respirable Particulate: 5.0 mg/m ³ 8-Hour TWA (OSHA)

*Values do not reflect absolute minimums and maximums; these values are typical which may vary from time to time.

WHMIS Classification: D2B, E

3 HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER!

HEALTH HAZARDS

MAY BE CORROSIVE TO THE SKIN, EYES AND RESPIRATORY TRACT

MAY BE HARMFUL IF SWALLOWED OR INHALED

**SEE "TOXICOLOGICAL INFORMATION" (SECTION 11) FOR MORE INFORMATION

FLAMMABILITY HAZARDS

DUSTS MAY BECOME EXPLOSIVE

REACTIVITY HAZARDS

STABLE

POTENTIAL HEALTH EFFECTS, SKIN

MODERATE TO SEVERELY IRRITATING. Contact with moist skin or membranes may cause burns. Contact with concentrated solutions of this product may cause burns. Contact may cause reddening, itching and inflammation.

May cause an allergic reaction in some individuals (sensitizer).

POTENTIAL HEALTH EFFECTS, EYE

CORROSIVE. Direct contact may cause pain, tears, burns, sensitivity to light, swelling and possible corneal damage.

POTENTIAL HEALTH EFFECTS, INHALATION

SLIGHTLY TO MODERATELY IRRITATING. Symptoms may include sore throat, coughing, labored breathing, sneezing and burning sensation, depending on the concentration and duration of exposure.

Overexposure to this material may cause systemic damage including target organ effects listed under "Toxicological Information" (Section 11).

POTENTIAL HEALTH EFFECTS, INGESTION

Ingestion of large amounts may cause gastrointestinal disturbances. May cause severe irritation with intense burning of the mouth and throat followed by abdominal pain and distress, nausea, vomiting, and diarrhea.

Overexposure to this material may cause systemic damage including target organ effects listed under "Toxicological Information" (Section 11).

4 FIRST AID MEASURES

SKIN

Immediately flush skin with plenty of water, for at least 15 minutes, while removing contaminated clothing and shoes. GET IMMEDIATE MEDICAL ATTENTION.

Place contaminated clothing in closed container for storage until laundered or discarded. If clothing is to be laundered, inform person performing operation of contaminant's hazardous properties. Discard contaminated leather goods.

EYE

Flush immediately with large amounts of water for at least 15 minutes. Eyelids should be held away from the eyeball to ensure thorough rinsing. GET IMMEDIATE MEDICAL ATTENTION.

INHALATION

Remove to fresh air. If not breathing, institute rescue breathing. If breathing is difficult, ensure airway is clear and give oxygen.

Keep affected person warm and at rest. GET IMMEDIATE MEDICAL ATTENTION.

INGESTION

Keep affected person warm and at rest. GET IMMEDIATE MEDICAL ATTENTION.

Never give anything by mouth to an unconscious person. Do not induce vomiting because of danger of aspirating liquid into lungs, causing serious damage and chemical pneumonitis.

Have victim rinse mouth thoroughly with water, then drink 2 to 8 oz. (60 to 240 ml) of water. If vomiting occurs naturally, have the victim lean forward to reduce risk of aspiration. Repeat administration of water. Quickly transport to emergency care facility.

NOTES TO PHYSICIAN

This product is primarily an irritant and corrosive. As a corrosive, give attention to potential complication of esophagus or stomach perforations if ingested. Use of emetics and lavage are contraindicated. Necrosis and associated inflammatory processes peak at about 48 hours, but may extend up to four days. Initial healing processes occur during the period 4 to 14 days, but the esophageal wall is weakest during this period.

If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

5 FIRE FIGHTING MEASURES

HAZARDOUS COMBUSTION PRODUCTS

Combustion may produce CO_x, oxides of sodium and phosphorus, and irritating vapors.

EXTINGUISHING MEDIA

Use dry chemical, alcohol foam, all purpose AFFF or carbon dioxide to extinguish fire.

BASIC FIRE FIGHTING PROCEDURES

Do not add water to acid. Water applied directly results in evolution of heat and splattering of acid. Acid can react with metals to liberate flammable hydrogen gas, especially when diluted with water. Evacuate area and fight fire from a safe distance.

Use water spray to cool adjacent structures and to protect personnel. When using water spray, use extreme caution! Acid solution is corrosive. Water or foam may cause frothing.

Dust dispersed by water stream in the presence of an ignition source could cause an explosion.

Firefighters must wear MSHA/NIOSH approved positive pressure breathing apparatus (SCBA) with full face mask and full protective equipment.

UNUSUAL FIRE & EXPLOSION HAZARDS

Airborne dust in sufficient concentrations when confined and exposed to a sufficient ignition source can explode

May melt, with loss of steam.

Flammability Limits for dust:

Lower: 0.28 kg/m³

Upper: 0.29 kg/m³

Flash Point

ND

Autoignition Temperature

ND

Flammability Limits in Air, Lower, % by Volume

SEE ABOVE

Flammability Limits in Air, Upper, % by Volume

SEE ABOVE

6 ACCIDENTAL RELEASE MEASURES

EMERGENCY ACTION

None

ENVIRONMENTAL PRECAUTIONS

If product is released to the environment, take immediate steps to stop and contain release. Caution should be exercised regarding personnel safety and exposure to the released product. Notify local, provincial and/or federal authorities, if required.

See Federal Regulations (Section 15).

SPILL OR LEAK PROCEDURE

Shovel into a container for later disposal. Avoid cleanup procedures that may result in water pollution. The very fine particles can cause a fire or explosion, eliminate all ignition sources.

Do not touch or walk through spilled material.

Avoid excessive generation of dust. If dust is generated, appropriate respiratory, eye and skin protection should be used to protect personnel during clean-up. Avoid contact with water.

Large spills may be neutralized with dilute alkaline solutions of soda ash or lime.

See Exposure Controls/Personal Protection (Section 8).

7 HANDLING & STORAGE

HANDLING

This material should be stored and shipped in plastic or plastic lined containers. Do not use with materials or equipment sensitive to acidic solutions.

Minimize dust generation during handling and contact.

Dusts may become explosive. Ground lines and equipment used during transfer to reduce the possibility of static spark-initiated fire or explosion. Use non-sparking tools. Do not cut, grind, drill, weld in the vicinity of the product or reuse containers unless adequate precautions are taken against these hazards.

Avoid inhaling dust and contact with skin and eyes.

Do not eat, drink or smoke in areas of use or storage.

STORAGE

Store in tightly closed containers in a cool, dry, isolated, well-ventilated area away from heat, sources of ignition and incompatibles. Avoid contact with strong oxidizers.

Empty containers may contain product residue. Do not reuse without adequate precautions.

Avoid contact with metals. Avoid excessive heat.

8 EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS

General or local exhaust ventilation and other forms of engineering controls are the preferred means for controlling exposures.

EYE PROTECTION: PERSONAL PROTECTION EQUIPMENT (PPE)

Wear chemical safety goggles and face shield. Have eye washing facilities readily available where eye contact can occur.

SKIN PROTECTION: PERSONAL PROTECTION EQUIPMENT (PPE)

Avoid skin contact with this material. If skin contact is anticipated, protective clothing, including impervious gloves, should be worn.

Additional protection may be necessary to prevent skin contact including use of apron, armcovers, face shield, or boots. Provide safety showers at any location where skin contact can occur.

Use good personal hygiene.

RESPIRATORY PROTECTION: PERSONAL PROTECTION EQUIPMENT (PPE)

A NIOSH/MSHA approved dust respirator should be used as a precautionary measure when airborne contaminants may occur, when there is a potential for uncontrolled release, or when exposure levels are not known.

9 PHYSICAL & CHEMICAL PROPERTIES

ODOR AND APPEARANCE

ODORLESS, PARTIALLY CRYSTALLINE SOLID; TRANSLUCENT OR OPAQUE WHITE

Boiling Point	NA
Specific Gravity	ND
Melting Point	ND
Percent Volatile	ND
Vapor Pressure	NA
Vapor Density	ND
Bulk Density	ND
Solubility in Water	SOLUBLE BUT MAY DISSOLVE SLOWLY
Octanol/Water Partn	ND
Volatile Organic	NA
Pour Point	NA
pH Value	NA
Freezing Point	ND
Viscosity	NA
Evaporation Rate	NA
Molecular Formula	MIXTURE
Molecular Weight	NA
Chemical Family	ORGANIC ACID
Odor Threshold	ODORLESS

10 STABILITY & REACTIVITY

STABILITY/INCOMPATIBILITY

Incompatible with metal nitrates, alkali carbonates, bicarbonates and oxidizers. Product may decompose upon heating. See precautions under Handling & Storage (Section 7).

HAZARDOUS REACTIONS/DECOMPOSITION PRODUCTS

Combustion may produce CO_x, oxides of sodium and phosphorus, and irritating vapors.

11 TOXICOLOGICAL INFORMATION

ROUTES OF EXPOSURE

Inhalation, ingestion, skin and eye contact.

LD50

LD50: 2-Hydroxy-1,2,3-Propanetricarboxylic Acid Rat Oral 3 g/kg.

LD50: Sodium hexametaphosphate Rat Oral, 6500 mg/kg

TOXICOLOGICAL DATA

Acute or chronic overexposure to this material or its components may cause systemic toxicity, including adverse effects to the following: skin, eye, kidneys and respiratory system.

Exposure to components of this material may cause the following specific symptoms, depending on the concentration and duration of exposure: erosion of teeth, headache and red, itchy skin (dermatitis).

PRE-EXISTING CONDITIONS AGGRAVATED BY EXPOSURE

Pre-existing medical conditions which may be aggravated by exposure include disorders of the skin, eye, respiratory and cardiovascular systems.

12 ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

ND

13 DISPOSAL CONSIDERATIONS

WASTE DISPOSAL

This product, as supplied, when discarded or disposed of, is a hazardous waste according to Federal Regulations due to its corrosivity.

In Canada, wastes should be disposed of according to federal, state, provincial and local regulations.

14 TRANSPORT INFORMATION

BILL OF LADING - BULK (U. S. DOT)

Corrosive Solid, Acidic, Organic, N.O.S. (2-Hydroxy-1,2,3-propanetricarboxylic acid), 8, UN 3261, PG II

BILL OF LADING - NON-BULK (U. S. DOT)

Corrosive Solid, Acidic, Organic, N.O.S. (2-Hydroxy-1,2,3-propanetricarboxylic acid), 8, UN 3261, PG II

The above description may not cover shipping in all cases, please consult 49 CFR 172.101 for specific shipping information.

15 REGULATORY INFORMATION

FEDERAL REGULATIONS

All components of this product are listed on the TSCA Inventory.

This material, as supplied, contains sodium hexametaphosphate a Hazardous Substance as per 40 CFR Part 302.4. The reportable quantity for sodium hexametaphosphate is 5,000 pound(s). Any release of this material that results in a release of sodium hexametaphosphate equal to or exceeding the reportable quantity must be reported to the National Response Center (800-424-8802) and appropriate state and local regulatory agencies as described in 40 CFR Part 302.6 and 40 CFR 355.40, respectively. Check state and local regulations for any additional requirements as these may be more restrictive than federal laws and regulations. Failure to report may result in substantial civil and criminal penalties.

This product does not contain toxic chemicals (in excess of the applicable de minimis concentration) that are subject to the annual toxic chemical release reporting requirements of the Superfund Amendments and Reauthorization Act (SARA) Section 313 (40 CFR 372).

There may be specific regulations at the local, regional or state/provincial level that pertain to this product.

SARA TITLE III RATINGS

Immediate Hazard: X Delayed Hazard: X Fire Hazard: X Pressure Hazard: -
Reactivity Hazard: -

STATE REGULATIONS

Based on available information this product does not contain any components or chemicals currently known to the State of California to cause cancer, birth defects or reproductive harm at levels which would be subject to Proposition 65. Reformulation, use or processing of this product may affect its composition and require re-evaluation.

PENNSYLVANIA - Non-hazardous ingredients present at >3%: None

INTERNATIONAL REGULATIONS

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and this MSDS contains all the information required by the CPR.

WHMIS Classification: D2B, E

All known major components of this product are listed on the Canadian DSL.

WHMIS RATINGS

Compressed Gas		Flammable/Combustible		Oxidizer		Acutely Toxic
Other Toxic Effects	X	Bio Hazardous		Corrosive	X	Dangerously Reactive

NFPA RATINGS

Health	3	Flammability	2	Reactivity	0	Special Hazards
--------	---	--------------	---	------------	---	-----------------

HMIS RATINGS*** - Indicates chronic health hazard**

Health	3*	Flammability	2	Reactivity	0
--------	----	--------------	---	------------	---

16 OTHER INFORMATION**DISCLAIMER**

NOTICE: The information presented herein is based on data considered to be accurate as of the date of preparation of this Material Safety Data Sheet. However, MSDS may not be used as a commercial specification sheet of manufacturer or seller, and no warranty or representation, expressed or implied, is made as to the accuracy or comprehensiveness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Current Revision Date 25-Jul-2012

Replaces Sheet Dated 10-Jun-2008

Completed By Koch Chemical Technology Group, LLC, call (978) 694-7346 or (978) 657-4250